

HADLEY Energy Services, Inc. is the premier equipment rental tool provider for the oil & Gas Industry in the Gulf of Mexico. Our quality policy is to provide our customers with products or services that meet or exceed their expectations and we've been doing just that for over 35 years!



CHICKSAN PACKAGES

INTERGAL PACKAGES

We have a complete inventory of Integral Iron and can accommodate virtually all of our customers' needs. We at HADLEY Energy Services, have multiple length trailers and baskets that are vital to our customers operation.

LAND APLICATIONS



OFFSHORE APLICATIONS





Iron & Spools

Iron (Standard & H2S)

- 1", 2" & 3" 1502 Straights and Pup Joints
- 90's
- Tee's
- Swings
- 2x1, 2x2, 3" Plug Valves (Manual & Hyd)
- Assorted 1502 Cross Overs
- Data Headers (2" & 3")
- Flow Cross (Studded & 1502)
- Check Valves (Dart)



Spacer Spools & Riser Spools 2', 4', 6', 8' & 10' Joints Available 2-1/16" – 7-1/16" (10k & 15K)



Plug Catchers – Land/Offshore 3"x2" 10k Bypass



Bowen Riser

4" Riser

2', 4', 6', 8' & 10' Joints Available





Valves

Gate Valves

- Hydraulic Gate Valve
- Assortment of Manual Gate Valves



Pneumatic (10k & 15k)



Plug Valves

• 2x1, 2x2, 3" Plug Valves (Manual & Hyd)





MANIFOLDS

By listening to the needs of our customers and peers over the last 35 plus years we've assembled a variety of manifold solutions. Although our series of dual choke, hydraulic and manual manifolds options cater to both the drilling side as well as work over and completion needs, we have lots of other options to meet the demands of our customers







2x1 Triangle Squeeze Manifolds

2" & 3" Dual Choke Manifolds

Gate Valve Manifolds

5 or 9 Valve w/ Manual or Hyd Chokes



Triplex Pumps

GD-600



- High Pressure Reciprocating GD600 & OFM600S triplex pumps
- •6135H John Deere Diesel Engine (550 HP)
- Eaton Fuller 10 speed manual transmission
- Split skid design: pump on one side & engine on other (can be lifted as one piece or two)
- Pump side: 6'X8'X8'3" (9,550 lbs.)
- Engine side: 11'6"X8'X8"3" (13,750lbs.)
- •3" or 5" plungers
- Includes as added safety digital over pressure shutdown system

GD-250



- • High Pressure Reciprocating GD250 Triplex Pump
- •6068H John Deere Diesel Engine (250 HP)
- Eaton Fuller 10 speed manual transmission
- •Single Skid Design
- • Skid: 14'6" X7' X7' (16,500 lbs.)
- •3" or 5" Plungers
- Includes as added safety digital over Pressure Shutdown System



Pumps

Air Operated

General Service - 1",2" & 3"



Acid – 2"



Diesel Pumps

• 3" Hydraulic Submersible

Trash Pumps – 2" & 3"





Centrifugal Pump

- 4x4 w/ Fig 100 Suction/Discharge
- Hoses Available Upon Request



Tanks

100 BBL Open Top

Gas Buster

2 - Hydraulic Blenders

3 - 35 BBL Compartments

4" Fig 100 Outlets

Dimensions: 19' x 8' x 9'9" (10,000 lbs)



50 BBL Open Top

Gas Buster

2 - Hydraulic Blenders

2 - 25 BBL Compartments

4" Fig 100 Outlets

Dimensions: 10'6" x 8' x 9'9" (5,500 lbs)



35 BBL Cement Blending Tank

Charge Pump Hydraulic Mixer 4" Fig 100 Outlet





Support Equipment

Light Plants

- Land
- Offshore Skid mount
- LED or Standard Lighting



Air Compressors

Offshore Skid Mount 185 CFM



Pressure Washers

- 3,500 PSI
- Diesel Engine
- Assorted Tips & Nozzles



Pressure Ratings up to 3000 lbs







Support Equipment

Bottle Racks

- Nitrogen
- Single Bottle to 12 Bottle



Fuel Tank

Skid Mount 12 Volt Pump w/ 75' Hose



Duel Filter Pot

- 2" & 3" Available
- 30 Bank Pots (15 Filters Each Pot)
- Hoses Available Upon request





Accumulators

- 3 to 9 Station Units
- **Air & Diesel Units**
- **Remote Panels**



80 Gal Balls

- Pre charged to 1,000 lbs
- 602 Unions
- Hoses Available Upon Request





VBR (Variable Bore Rams)

VBR Types

- Cameron Type U
- Shaffer Style SL
- Hydrill Type X
- Certified Rams & Non-Certified



